

LockitFamily data sheet

Status: 09/2023



	NanoLockit	Lockit	LockitSlate Take2	Lockit +
Connectivity				
Wireless	ACN –	ACN –	ACN –	ACN WiFi
Timecode & ACN	Lemo	Lemo (blue)	Lemo (blue)	Lemo front (blue) Lemo (standard extension)
Trilevel Sync / Wordclock	–	Lemo (yellow)	–	Lemo front (yellow)
USB-Socket	Micro USB	USB-C	USB-C	USB-A, USB-C
Midi Timecode	yes	yes	yes	<i>future feature</i>
Display	–	yes	yes	yes
Auto C-Jam	–	–	–	yes
3 Buttons	yes	yes	yes	yes
Single Jam (1 Frame in 3Days)	yes	yes	yes	yes
C-Jam Green+Power	–	yes	yes	yes
TX Mode Red+Power	yes	yes	yes	yes
Quick Access	TC Level/ LED Brightness	–	–	–
Device Menu	–	Project Frame Rate (23.976, 24, 25, 29.97, 29.97D, 30 + double frame rates) Sync Format (off, PsF, P, i, wordclock 48, 96, 192 kHz - only Lockit / Lockit+) Select ACN Channel (off, 11 - 26) TC Start Preference (RTC, RTC-12, zero, one, manual) TC & Sync Offset (-10,00 ... 10.00 frames) TC Out Level (only Lockit) Show UB on Clap, Show Clapped TC, Show Running TC (only LockitSlate Take 2) LED Brightness Autopower		
WebInterface	–	–	–	Advanced Timecode Settings (e.g. UserBits, DateFormat, ...) ACN Radar RadioWizard Sound Report Lens Data
Toolbox via USB	Date Format Set RTC (NanoLockit, Lockit) Firmware Update Project Frame Rate (23.976, 24, 25, 29.97, 29.97D, 30 + double frame rates) Select ACN Channel (off, 11 - 26) LED Brightness Sync Format (Lockit) TC Out Level (NanoLockit, Lockit)			–
Size	65.5 mm x 36,5 mm x 21 mm	65.6 mm x 44.0 mm x 20.0 mm	210 mm x 65 mm x 27 mm	
Weight	72 g	80 g	450 g	
Battery	internal	1 x NP50	4 x AA (NiMH)	2 x BX1
Ext Power	USB	USB	USB	USB / HiRose
Duration	25h+	17h	17h (2500mAh)	

To get your own Lockit go to ambient.de
 Please visit also faq.ambient.de for frequent questions on Timecode or our Timecode Cable Guide.

Get the latest firmware ambient.de/downloads